

# RX

**ACCUREX**



## Nimble and functional industrial scale

Highly suitable for checking the weight of boxes with product, sacks, packages as well as the weighing of mixes and additives.

- Platform with a tubular structure in painted steel, with plate and column in stainless steel.
- Load sensor in aluminium with IP65 protection.
- Column 620 or 820 mm in height (depending on model).
- 7-segment LED display, 20 mm in height.
- Indicator casing in ABS with IP 54 protection.
- Rechargeable internal battery with 24- to 50-hour life.
- Power supply included for powering up and charging the battery.
- External calibration adjustment.

## Operational functions

- Setting to zero.
- Taring of receptacles with tare memory.



## Technical characteristics

Model	RX-30S	RX-60S	RX-150S	RX-60M	RX-150M	RX-300M	RX-150L	RX-300L
Capacity (kg)	30	60	150	60	150	300	150	300
Resolution (g)	5	10	20	10	20	50	20	50
Weighing units	kg							
Material of the structure	lacquered steel							
Material of the plate	stainless steel							
Indicator material	ABS							
Platform dimensions (mm)	300 x 500			400 x 600			450 x 700	
Plate dimensions (mm)	300 x 400			400 x 500			450 x 600	
Indicator dimensions (mm)	255 x 165 x 110			255 x 165 x 110			255 x 165 x 110	
Platform height (mm)	85			110			120	
Total height (mm)	620			620			820	
Indicator net weight (kg)	1.2			1.2			1.2	
Platform net weight (kg)	4.1			7.9			9.7	
Dim. with indicator packaging (mm)	280 x 185 x 190			280 x 185 x 190			280 x 185 x 190	
Dim. with platform packaging (mm)	700 x 550 x 135			600 x 500 x 120			500 x 400 x 105	
Total weight with indicator packaging (kg)	1.5			1.5			1.5	
Total weight with platform packaging (kg)	4.8			8.7			10.9	

## External dimensions (mm)

